



WOOD SEALER

AQUA Tite Wood Sealer is a gel treatment that seals, waterproofs, hardens and preserves most wood products. The catalyst in Wood Sealer reacts with both the acid and the alkali present in most wood, forming an internal seal and water barrier. It will not alter the physical characteristics of the natural wooden surface to which it is applied. Wood Sealer works internally with the wood leaving a bondable surface and will extend the life of your wood with a one-time treatment.

Make your space AQUA Tite

1 GALLON (3.785 LITERS)

MADE IN THE USA



SURFACE PREPARATION:

Normal Surfaces and/or bare wood need no prior preparation. If mill glaze is present, remove before application for better penetration. Any paint or surface treatment must first be REMOVED for Wood Sealer to penetrate and be effective. Remove by scraping, grinding, and/or applying suitable coating removers/strippers. Wood Sealer is best applied in temperature conditions above freezing.

Dampening wood prior to application will aid in penetration. Very old and "restored wood" can be "primed" with baking soda and water.

APPLICATION INSTRUCTIONS:

1. **Dilute Wood Sealer by adding 20-40% Water...e.g., add 1-2 gallons of water to 5 gallons Wood Sealer.** 2. **SHAKE WELL BEFORE USING.** Apply using pump up sprayer. 3. Normal applications only need one coat depending upon porosity. Apply liberally and saturate all areas. On vertical walls, apply from the bottom up. 4. In special problem areas where excessive moisture or water seepage is present, additional coatings may be required. Excessive coatings will not penetrate and will remain gummy on the surface. Such excess should be removed before hardening using water and a squeegee. 5. Do not allow puddles to dry on the surface. Broom or brush out puddles so all material soaks in completely. 6. Clean with water. If discoloration occurs due to acids or contaminants being pushed out of the wood, rinse with a light solution of oxalic, phosphoric, citric acid or vinegar or any "wood brightener" to return wood to original coloration. Rinse acid wash with water. Call or email for instructions on very old wood.

Do not apply to glass, glazed surfaces, or aluminum, as etching will occur. In case of accidental contact; rinse thoroughly with water immediately. Wood Sealer is not meant to fill or seal visible cracks. For surfaces not specified above, we recommend that Wood Sealer be applied to a small test area first.

If Wood Sealer is frozen, thaw completely before using. Freezing will not harm the product. Wood Sealer is NOT a "wood finish" and does not leave a surface coating...it is an INTERNAL protector

COVERAGE: (Actual coverage will depend upon porosity of surface.) 1 Gallon treats 150-200 sq. ft.

WARNING: May cause an allergic reaction. May cause eye or skin irritation. May be harmful if swallowed.

FIRST AID TREATMENT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, seek medical attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, seek medical advice. Wash contaminated clothes before wearing again. IF SWALLOWED: Rinse mouth and throat thoroughly with water. Call POISON CONTROL or seek medical advice if you feel unwell. Keep out of reach of children.

For further safety information, please refer to the Safety Data Sheets available at www.aquatiteusa.com

SHAKE WELL BEFORE USING.

Distributed by:

Manufactured by:



235 WEST ROAD STE 3
PORTSMOUTH, NH 03801
1-603-431-5555

- ◆ Non-Toxic
- ◆ Non-Flammable
- ◆ Fumeless
- ◆ Safe
- ◆ Easy To Use